SSP SPECIFIC HAZARD ATTACHMENT: SMALL BOATS

re safety briefing from boat crew operators re emergency extrication briefing location of emergency equipment e operator knows how to contact emergency services e operator has good communications with coordinating vessels and shore units e communications schedule with parent unit is understood e distress signals are available for day and night operations (3 per shift) e qualified operators are running the boats e appropriate number of CG-approved type I and Type II preservers m location of safe seating from boat operator e portable fuel tanks are full prior to boarding full sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
location of emergency equipment e operator knows how to contact emergency services e operator has good communications with coordinating vessels and shore units e communications schedule with parent unit is understood e distress signals are available for day and night operations (3 per shift) e qualified operators are running the boats e appropriate number of CG-approved type I and Type II preservers m location of safe seating from boat operator e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e operator knows how to contact emergency services e operator has good communications with coordinating vessels and shore units e communications schedule with parent unit is understood e distress signals are available for day and night operations (3 per shift) e qualified operators are running the boats e appropriate number of CG-approved type I and Type II preservers m location of safe seating from boat operator e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e operator has good communications with coordinating vessels and shore units communications schedule with parent unit is understood e distress signals are available for day and night operations (3 per shift) e qualified operators are running the boats appropriate number of CG-approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type I and Type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operator approved type II preservers no location of safe seating from boat operato
e communications schedule with parent unit is understood e distress signals are available for day and night operations (3 per shift) e qualified operators are running the boats e appropriate number of CG-approved type I and Type II preservers in location of safe seating from boat operator e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e distress signals are available for day and night operations (3 per shift) e qualified operators are running the boats e appropriate number of CG-approved type I and Type II preservers m location of safe seating from boat operator e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e qualified operators are running the boats e appropriate number of CG-approved type I and Type II preservers in location of safe seating from boat operator e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e appropriate number of CG-approved type I and Type II preservers in location of safe seating from boat operator e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
m location of safe seating from boat operator e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e portable fuel tanks are full prior to boarding all sources of ignition away from fueling area boat does not exceed safe load capacity (personnel plus equipment) by proper footwear for maintaining adequate boat deck contact
all sources of ignition away from fueling area e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e boat does not exceed safe load capacity (personnel plus equipment) e proper footwear for maintaining adequate boat deck contact
e equipment on boat is distributed evenly to ensure stability
e at least two people are operating the boat
e sun protection is available (sun glasses and sun screen)
e adequate food and water is available for the duration of the operation
e presence of first-aid kits, fire extinguishers, and alternate means of propulsion
e adequate fenders and mooring lines are available.
n seated whenever possible – Keep low in the boat
e boat is able to maintain direct contact visually or by radio
anchoring the boat by the stern
nands and feet away form pinch points between boat and dock
lear of lines being used for mooring
disembark with bulky or heavy equipment; get assistance
ssisting in the mooring operation, remain seated until lines are tied.

Small Boat Hazard Attachment RI DEM ERP 7C13